

Designed with simplicity in mind, the NU2 range hood models are made to exacting standards and offer the most for the money.

SIZE	WHITE	STAINLESS	GREASE FILTER (replacement)	CHARCOAL FILTER
24 in.	NU224WW	-	BP29	41F
30 in.	NU230WW	NU230SS	BP29	41F

PERFORMANCE				
Duct Orientation	Size	Damper	Sones on high speed	CFM on high speed
Vertical - Rectangular	3¼ in. x 10 in.	Included	6.5	160
Horizontal - Rectangular	3¼ in. x 10 in.	Included	6.5	160

FEATURES	
Control type	2-speed rocker switch
Delay off	no
Filter Clean Reminder	no
Heat Sentry™	no
Lighting	1-level 75-watt bulb (not included)
Grease Filter	Aluminum (Qty. 1)
ENERGY STAR®	no
Recirculation	Charcoal filter sold separately



AC INPUT	
120 V, 60 Hz - 2.5 AMPS	

OPTIONAL ACCESSORIES	
3¼ in. x 10 in. to 6-in. Round Duct Transition	411
7-in. Round Damper	BP87Q
7-in. Round Adapter Plate	SR680508

MOUNTING HEIGHT	
18 in. to 24 in. from cooktop to bottom of hood	

LIMITED WARRANTY	
1-year (See installation manual for full warranty text.)	

FOR INDOOR USE ONLY



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

99045921B